

Care instructions



For Metallised and Black-out materials

For all metallised fabrics as well as coated blackout materials simply wipe down gently with a cloth. Do not rub!

For all other fabrics

The pleated Cosiflor fabrics are easy to clean. Simply remove the blind from the window and wash the Cosiflor pleated fabrics using a mild detergent solution and water at approx. 30°C. Rinse thoroughly, fold the fabric parcel together and squeeze the water out by pressing the rails of the blind together until the blind is no longer dripping wet.

Hang up damp and leave closed to dry, but open and close the pleated blind several times during the drying process to prevent the pleats sticking together.

Do not iron.

In the case of electrical and side winder systems, make sure the mechanical/electrical parts do not come into contact with the detergent solution or water.

For pretensioned types, tension shoes must not be removed from the cords.

Important

When cleaning window frames and glass do not use any caustic or alkaline agents which could come into direct or indirect contact (condensation) with the system.

Condensation can form if there is too little ventilation or air flow.

We do not accept liability for fabric damage caused by water stains or insects.

Cosiflor pleated blinds are only suitable for use in heated indoor areas and conservatories and have not been designed for outdoor use or swimming pool enclosures.

For more details about cleaning specifications for individual fabrics contact your local dealer.

We advise against chemical or ultrasonic cleaning and do not accept warranty claims in this case.

Electric systems are not suitable for installation in humid areas.

Tip:

Daily use of your Cosiflor pleated blind will keep it in top condition for years of satisfaction.

